



Venta de Maquinaria Industrial y Agrícola  
 Km 24 Carr. Alvaro Obregón  
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412  
 Cels: (625) 590 8941 - (625) 115 4764 - (625) 134 4523  
 Cels: (625) 100 1010 - (625) 283 9741  
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 11128

**MARTILLO HIDRUALICO PARA MINICARGADOR**

BOBCAT

B950



Breaker	B700	B850	B950
Impact Energy Class	150 ft.-lb. (200 J)	300 ft.-lb. (400 J)	500 ft.-lb. (650 J)
DIMA Tool Energy Rating	125 ft.-lb. (169 J)	189 ft.-lb. (256 J)	212 ft.-lb. (287 J)
Blows per Minute	960 @ 8 GPM (30 LPM)	1100 @ 18 GPM (68 LPM)	1280 @ 20 GPM (76 LPM)
Flow Requirements	6-15 GPM (23-57 LPM)	11-18 GPM (42-68 LPM)	15-22 GPM (59-83 LPM)
Breaker w/Tool Point & X-Change Frame Weight	320 lb. (145 kg)	620 lb. (281 kg)	630 lb. (286 kg)
Loader Bob-Tach Frame Weight	203 lb. (92 kg)	203 lb. (92 kg)	203 lb. (92 kg)
Backhoe/Excavator X-Change Mount	Included w/Breaker	Included w/Breaker	Included w/Breaker
Tool Working Length	10 in. (254 mm)	11 in. (279 mm)	11 in. (279 mm)
Tool Diameter	1.96 in. (49.8 mm)	2.4 in. (61.0 mm)	2.4 in. (61.0 mm)
Recommended Working Thickness	2-4 in. (50-200 mm)	4-10 in. (100-250 mm)	6-14 in. (150-350 mm)
Demolished Volume per Hour*			
Non-Reinforced	1-4 yd <sup>3</sup> /hr (1.8-3.1 m <sup>3</sup> /hr)	4-12 yd <sup>3</sup> /hr (3.1-9.2 m <sup>3</sup> /hr)	5-15 yd <sup>3</sup> /hr (3.8-11.5 m <sup>3</sup> /hr)
Reinforced	1-3 yd <sup>3</sup> /hr (1.8-2.3 m <sup>3</sup> /hr)	1-4 yd <sup>3</sup> /hr (1.8-3.1 m <sup>3</sup> /hr)	2-6 yd <sup>3</sup> /hr (1.5-4.6 m <sup>3</sup> /hr)

A, No. Serie: