



- Venta de Maquinaria Industrial y Agrícola -
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: 625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 11128

MARTILLO HIDRUALICO PARA MINICARGADOR

BOBCAT

B950



Breaker	B700	B850	B950
Impact Energy Class	150 ft.-lb. (200 J)	300 ft.-lb. (400 J)	500 ft.-lb. (650 J)
CIMA Tool Energy Rating	125 ft.-lb. (169 J)	189 ft.-lb. (256 J)	212 ft.-lb. (287 J)
Blows per Minute	960 @ 8 GPM (30 LPM)	1100 @ 18 GPM (68 LPM)	1280 @ 20 GPM (76 LPM)
Flow Requirements	6-15 GPM (23-57 LPM)	11-18 GPM (42-68 LPM)	15-22 GPM (59-83 LPM)
Breaker w/Hail Point & X-Change Frame Weight	220 lb. (145 kg)	620 lb. (281 kg)	630 lb. (286 kg)
Loader Bob-Tach Frame Weight	203 lb. (92 kg)	203 lb. (92 kg)	203 lb. (92 kg)
Backhoe/Excavator X-Change Mount	Included w/Breaker	Included w/Breaker	Included w/Breaker
Tool Working Length	10 in. (254 mm)	11 in. (279 mm)	11 in. (279 mm)
Tool Diameter	1.96 in. (49.8 mm)	2.4 in. (61.0 mm)	2.4 in. (61.0 mm)
Recommended Working Thickness	2-4 in. (50-200 mm)	4-10 in. (100-250 mm)	6-14 in. (150-350 mm)
Demolished Volume per Hour, Non-Reinforced	1-4 yd ³ /hr (8-3.1 m ³ /hr)	4-12 yd ³ /hr (3.1-9.2 m ³ /hr)	5-15 yd ³ /hr (3.8-11.5 m ³ /hr)
Reinforced	1-3 yd ³ /hr (8-2.3 m ³ /hr)	1-4 yd ³ /hr (8-3.1 m ³ /hr)	2-6 yd ³ /hr (1.5-4.6 m ³ /hr)

Precio: 4,750.00 USD mas IVA

A, No. Serie: