



Venta de Maquinaria Industrial y Agrícola  
 Km 24 Carr. Alvaro Obregón  
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412  
 Cels: (625) 590 8941 - (625) 115 4764 - (625) 134 4523  
 Cels: (625) 100 1010 - (625) 283 9741  
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 14070

MAULDIN 1750C

MAULDIN

1750C

2006

625-F-75TJS6Y2-01625



1750-C SUPER PAVER			
<b>TRANSMISSION</b>		MAULDIN Super Steer™ with Power Assist™	
<b>OPERATION</b>		Tandem Hydrostatic	
<b>OPERATION</b>			
Length	19'0"	483 cm	
Width, Hopper In	8'0"	244 cm	
Width, Hopper Out	16'0"	488 cm	
Height	9'11"	279 cm	
Track Clearance	3'0"	91 cm	
<b>WEIGHT</b>			
Crawler Track	18,500 lbs	8,164 kg	
<b>HOPPER</b>		Capacity	
		8.0 tons (7,257 kg)	
<b>CRAWLER TRACK SUSPENSION</b>		Track Clearance, Width	
		8'0" / 18.3 cm	
Length, per side	8'0"	244 cm	
Drive	Automatic/Hydrostatic	<b>SCREENS</b>	
Track Rollers (each)	(1) Of Fixed, Metal Fixed	Type	
Wear Rollers (each)	(2) Of Fixed, Metal Fixed	SEVERA 96™	
		Free Floating, Vibration	
		Screen Plate	
		3'6" x 1'6" Box-On	
		Screen Depth	
		0" - 8"	
		Standard Width	
		8'	
		2.4 m	
		Standard Extension Width	
		16'0"	
		4.9 m	
		Full Extension Width	
		19'0"	
		5.8 m	
		Vertical Lift	
		3'0"	
		91 cm	
<b>HP (SAE/ISO)</b>		83 Standard - 88 Optional	
		C-Correction Equipment	
		3'	
		76 cm	
<b>Mixwidths</b>		Material Auger Diameter	
		9"	
		23 cm	
<b>Type and Cooling</b>		Auger System	
		(S)	
		Fixed Mounted	
<b>Electrical System</b>		(C)	
		Removable	
		Screen Heating	
		(S)	
		Screen	
		4 or Main Screen 2 on Extensions	
<b>CAPACITIES</b>		Fuel Tank	
		23 gal / 88 L	
		Hydraulic Tank	
		25 gal / 118 L	
		Washdown Tank	
		7.5 gal / 28 L	
		<b>OPTIONS</b>	
		C-Confidence Top, Propeller	
		Auto Throttle, Electric	
		Heating Straps	
		4 or Main Screen 2 on Extensions	
		<b>OPTIONAL</b>	
		Electric Heat Screen, Road Crew Kit, Screen Removable, Truck Hitch, In-Place Sunshade, Speed Automation	

CON MOTOR JOHN DEERE 4045DF150 A DIESEL 4 CILINDROS DE 80 HP. DE 8 FT DE ANCHO Y EXTIENDE HASTA 16 FT. CAPACIDAD DE TOLVA DE 8.0 TONELADAS, PESO 15,699.2 LBS,