



- Venta de Maquinaria Industrial y Agrícola -
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: 625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 14559

DETERCTOR DE GASES

EAGLE

71-0028RK

0000

0



Specifications

Table 1 lists physical and environmental specifications for the Eagle.
 Table 2 lists specifications for the Eagle's standard sensors.

	Table 1: Eagle Specifications
Target Gases ¹	Combustible gas; Oxygen (O ₂); Carbon monoxide (CO); Hydrogen sulfide (H ₂ S)
Case	High-impact polycarbonate-polyester blend
Safety/Regulatory ²	CSA/NRTL and UL, classified intrinsically safe (Class I, Division 1, Groups A, B, C, and D)
Dimensions	10.5 in. x 5.9 in. x 7.0 in. (26.7 cm x 15.0 cm x 17.8 cm)
Weight	5 lbs. (2.25 kg)
Power	Four D-size batteries (alkaline or Ni-Cd)
Continuous Operating Hours	Alkaline: 30 hours (minimum) Ni-Cd: 18 hours (minimum) ³
Operating Temperature	14°F to 104°F (-10°C to 40°C)
Humidity	0 to 95% (non-condensing)
Standard Accessories	Shoulder strap; alkaline batteries; hydrophobic probe; 5-foot hose
Optional Accessories	Ni-Cd batteries; battery charger (115 VAC); continuous operation adapter (115 VAC or 12 VDC); dilution fitting (1:1 or 3:1); remote alarm; data logger

1 Appendix C, D, and E describe the Eagle non-standard sensors.
 2 Consult H&E Instruments, Inc. for regulatory classifications of versions other than the standard 4-gas and non-standard toxic gas versions.
 3 Based on 190 part number 49-2409K.



DETECTOR DE GASES CON COMPUTADORA PORTATIL Y ACCESORIOS,
 (SPECIFICACIONES VER IMAGEN), - -