



- Venta de Maquinaria Industrial y Agrícola -
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: 625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 15026

HIDROTRACK

INGERSOLL RAND

ECM-720

0000

G72348JK



ENGINE	US (METRIC)
Type	C12 C-12 Tier 4 emissions compliant
Rated Power	346 hp (254 kW)
Operating Speed	1,500 rpm
Fuel Capacity	116 gal (437 l)
Operating Time	13.5 hour with fuel without refueling in most applications
COMPRESSOR	
Type	Oil flooded rotary vane
Value	400 cfm (11.3 m ³ /min)
Pressure	130 psig (8.9 bar)
BOOM & GUIDE	
Boom Length	32' 11" (10.04 m) with boom incl; 32' 0" (9.80 m) with boom hoist
Max Boom Swing	40° right / 30° left
Max Vertical Boom Movement	20° up / 50° down
Max Guide Swing	20° right / 30° left
Max Guide Range	130'
Boom Extension	2' (610 mm)
Guide Extension	1' (305 mm)
Overall Guide Length	27' 8" (8.4 m)
HC-200A DRIFTER	
Roll Size	100 mm (3.9 in) optional
Roll Diameter	508 mm (19.9 in) Roll range 4" - 9" (102 mm - 229 mm) - 8" (192 mm) roll optional
Rolls Per Foot	Standard
GENERAL SPECIFICATIONS	
Capacity	30' (9.1 m)
Operating Speed	17' (5.2 m/hr)
Rated Output	17' (5.2 m)
Track Clearance	12" (305 mm)
Roll Diameter	100 mm (3.9 in) optional
Roll Length	32' 0" (9.8 m) (9.8 m) (32' 0" (9.8 m))
Shipping Dimensions L x W x H	32' 0" x 8' 0" x 10' 0" (9.8 m x 2.4 m x 3.0 m)
Shipping Weight	40,000 to 50,000 kg
CAW & CONTROLS	
Safety and Control	Control ROPS/OPS with air conditioning and heat
Roll-over	ROPS roll-over
Control	Full hydraulic, fulling and lowering
	Direct feedback positioning
HYDRAULICS	
Hydro-Gen Hydraulic Control System	
Hydro-Gen System and Separation of Percussive Hoses for Superior Hose Management	
Hydraulic System Feed Pumps for Easy Trouble Shooting	
Hydraulic Controller	



CON MOTOR CATERPILLAR C12, MASTIL DE 28 FT, PISTOLA MONTALBERT HC200A, UTILIZA BARRAS DE 12X2, DIAMETRO DE PERFORACION DE 4 A 5 1/2 PULGADAS, , - -