



- Venta de Maquinaria Industrial y Agrícola -
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: 625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 15620

COMPACTADOR VOLVO DD24

VOLVO

DD24

0000

VCE00D24P0S2751



		DD22	DD24
Machine Weights (w/ 8000L)			
Shipping Weight	kg (lb)	2 850 (6 280)	3 000 (6 700)
Weight @ Rear Drum	kg (lb)	1 220 (2 700)	1 300 (2 860)
Weight @ Rear Drum	kg (lb)	1 550 (3 420)	1 300 (2 860)
Shipping Weight	kg (lb)	2 940 (6 480)	3 000 (6 700)
Machine Dimensions			
Length	mm (ft)	2 450 (8.0)	2 450 (8.0)
Height	mm (ft)	1 200 (3.9)	1 200 (3.9)
Height (top of steering wheel)	mm (ft)	1 040 (3.4)	1 040 (3.4)
Height (top of canopy)	mm (ft)	2 450 (7.9)	2 450 (7.9)
Depth (back)	mm (ft)	1 300 (4.3)	1 300 (4.3)
Track Clearance	mm (ft)	400 (13.1)	400 (13.1)
Depth (turning radius (to drum edge))	mm (ft)	2 000 (6.6)	2 000 (6.6)
Drum			
Width	mm (ft)	1 040 (3.4)	1 040 (3.4)
Offset	mm (ft)	100 (0.3)	100 (0.3)
Roll Protection	mm (ft)	13 800	13 800
Protection			
Height (top)	mm (ft)	55 7 (182.8) / 4 300	55 7 (182.8) / 4 300
Internal Amplitude	mm (ft)	620 (2.0)	620 (2.0)
Centerline Clearance	mm (ft)	37 (1.2)	40 (1.3)
Clearance	mm (ft)	25 (0.8)	25 (0.8)
Performance			
Type		Direct Fuel Injection	Direct Fuel Injection
Drive Type		Roller Drive	Roller Drive
Rated Speed	km/h (mph)	0 - 10 (0) - 4.0	0 - 10 (0) - 4.0
Capacity			
Motor / Motor		Cummins ISB1700	Cummins ISB1700
Engine Type		3-cylinder Diesel	3-cylinder Diesel
Rated Power @ Installed Speed	kW (hp)	24 (33)	24 (33)
Engine Fuel		17 vol% 1.4 alternative	17 vol% 1.4 alternative
Drum			
Roller		Roller	Roller
Roller Width		Spring loaded, 48 in. roller on each drum	Spring loaded, 48 in. roller on each drum
Roller Type		Protektor	Protektor
Roller		4 per drum	4 per drum
Roller		300 mm (11.8 in.) roller	300 mm (11.8 in.) roller
Drum Weight		Spring loaded, with rotating surface support	Spring loaded, with rotating surface support
Roller Weight		200 (440)	200 (440)
Dimensions			
Roller Width		4,730"	4,730"
Roller Height		4,730"	4,730"
Roller Clearance		60 (1.9)	60 (1.9)
Roller Clearance		27 (0.9)	27 (0.9)

CON MOTOR CUMMINS A 1700 A DIESEL DE 3 CILINDROS, RODILLOS COMPACTADORES DE 48 PULGADAS, PESO 5, 400 LBS, - -