



- Venta de Maquinaria Industrial y Agrícola -
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: 625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 15796

COMPACTADOR DE PLANCHA STANLEY HS6000

STANLEY

HS6000

0000

1313



SPECIFICATIONS

Performance	
Centrifugal Force	6400 lb/2803 kg
Developed Frequency	2000 rpm
Dimensions and Weights	
Spaced Between Pins	14 in./355.6 cm
Baseplate Size	26 in./661 cm
Overall Length	34 in./86 cm
Width Inside Bracket	10.25 in./261 cm
Overall Width	23.5 in./60 cm
Overall Height	27.5 in./70 cm
Weight	850 lb/386 kg
Standard Mounting Pin Diameter	Universal

*Contact your dealer for appropriate mounting hardware for your application.

Hydraulic Requirements	
Minimum Flow	12 gpm/45 lpm
Maximum Flow	25 gpm/95 lpm
Optimum Flow	13 gpm/49 lpm
Normal Operating Pressure	2000 psi/138 bar
Back Pressure	Not to Exceed 250 psi/17 bar
Relief Setting	2500 psi/172 bar

Miscellaneous		Part Number			
Flow Meter		29835			
TORQUE TABLE					
General Item No.	Swivel Top Item No.	Description	Apply	Ft.Lb.	Nm
27		HHCS 3/8-16 UNC Grade 8	Anti-Seize	35	47
3, 15, 22	8	HHCS 1/2-13 UNC Grade 8	Anti-Seize	75	101
31		HHCS 3/4-13 UNC Grade 8	Anti-Seize	85	115
25	1	HHCS 5/8-11 UNC Grade 8	Anti-Seize	100	244

PLANCHA COMPACTADORA DE 30X22, COMPACTADOR PARA RETROEXCAVADORA,
 PESO 850 LBS, - -