



Venta de Maquinaria Industrial y Agrícola
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: (625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 15796

COMPACTADOR DE PLANCHA STANLEY HS6000

STANLEY

HS6000

0000

1313



SPECIFICATIONS					
Performance					
Centrifugal Force	8400 lb/2003 kg				
Developed Frequency	2000 rpm				
Dimensions and Weights					
Spread Between Pins	14 in/35.6 cm				
Bolesplate Size	26 in/66 cm				
Overall Length	34 in/86 cm				
Width Inside Bracket	10.25 in/26 cm				
Overall Width	23.5 in/59 cm				
Overall Height	27.5 in/70 cm				
Weight	850 lb/388 kg				
Standard Mounting Pin Diameter	Universal*				
*Contact your dealer for appropriate mounting hardware for your application.					
Hydraulic Requirements					
Minimum Flow	12 gpm/45 lpm				
Maximum Flow	25 gpm/95 lpm				
Optimum Flow	13 gpm/49 lpm				
Normal Operating Pressure	2000 psi/138 bar				
Back Pressure	Not to Exceed 250 psi/17 bar				
Relief Setting	2500 psi/172 bar				
Miscellaneous					
Flow Meter	Part Number 26885				
TORQUE TABLE					
General Item No.	Saeel Top Item No.	Description	Apply	Ft.Lb.	Nm
27		HHCS 3/8-16 UNC Grade 8	Anti-Seize	35	47
3, 15, 22	8	HHCS 1/2-13 UNC Grade 5	Anti-Seize	75	101
31		HHCS 1/2-13 UNC Grade 8	Anti-Seize	85	115
25	1	HHCS 5/8-11 UNC Grade 8	Anti-Seize	180	244

PLANCHA COMPACTADORA DE 30X22, COMPACTADOR PARA RETROEXCAVDAORA,
 PESO 850 LBS, - -