



Venta de Maquinaria Industrial y Agrícola
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: (625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 15827

MOTOR DIESEL DETROIT 12V-71

DETROIT

12V-71

0000

SIN NUMERO DE SERIE



DETROIT 12V-71 & 16V-71 SPECS

Note - horsepower and torque figures often varied considerably by application and the following values are an approximate range of available ratings:

	12V-71N, 12V-71T, 12V-71TA	16V-71N, 16V-71T, 16V-71TA
Manufacturer:	Detroit Diesel	
Application:	Overhighway, emergency services, generator sets, motorhomes, transit buses, agricultural equipment, industrial, military	
Configuration:	V-12	V-16
Type:	2 cycle diesel	2 cycle diesel
Displacement:	362.66 (13.97 liters)	1,126.66 (68.62 liters)
Compression:	17.0:1 (12V-71T, 12V-71TA) 18.7:1 (12V-71N)	17.0:1 (16V-71T, 16V-71TA) 18.7:1 (16V-71N)
Bore:	4.25 in (108 mm)	4.25 in (108 mm)
Stroke:	5.00 in (127 mm)	5.00 in (127 mm)
Injection:	Mechanical unit injector fuel system	
Aspiration:	Naturally aspirated (12V-71N) and turbocharged (12V-71T, 12V-71TA) versions produced. All engines feature a root type blower to provide exhaust gas scavenging.	Naturally aspirated (16V-71N) and turbocharged (16V-71T, 16V-71TA) versions produced. All engines feature a root type blower to provide exhaust gas scavenging.
Oil Capacity:	Varies by application	
Weight:	3,800 - 4,000 lbs	4,600 - 4,800 lbs
Peak Horsepower:	400 - 800 hp @ 2,100 - 2,300 rpm	630 - 700 hp @ 2,100 rpm
Peak Torque:	1,200 - 1,750 b-ft @ 1,200 - 1,400 rpm	1,700 - 2,200 b-ft @ 1,200 - 1,400 rpm



A DIESEL 12 CILINDROS, DETROIT 12V-71, TRANSMISION ALLISON 6061, - -