



Venta de Maquinaria Industrial y Agrícola
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: (625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 16312

TRITURADORA DE CONO TELSMITH 36FC

TELSMITH

36FC

0000

6774



| SIZE | 24 FC (2 Ft.) | | | 36 FC (3 Ft.) | | | 48 FC (4 Ft.) | | | 66 FC (5 1/2 Ft.) | | |
|---|---------------|--------|--------|---------------|--------|--------|---------------|--------|--------|-------------------|--------|--------|
| | Coarse | Medium | Fine | Coarse | Medium | Fine | Coarse | Medium | Fine | Coarse | Medium | Fine |
| Feed Opening "D" Open Side | 2 1/4" | 1 3/4" | 1 3/8" | 3" | 2" | 1 1/2" | 4 1/8" | 3" | 2 1/2" | 5 1/4" | 4 1/2" | 3" |
| Feed Opening "E" Closed Side | 1 7/8" | 1 1/4" | 1 1/2" | 2" | 1 1/4" | 1 1/4" | 3" | 1 3/4" | 1 1" | 4" | 2 1/2" | 1 3/4" |
| Recommended Min. Discharge Opening "F" | 1/4" | 3/16" | 1/8" | 3/8" | 1/4" | 3/16" | 3/8" | 1/4" | 1/4" | 1/2" | 3/8" | 3/8" |
| Capacities in Tons Per Hour at Indicated Discharge Opening "F"; Tons of 2000 Lbs. Material Weighing 100 Lbs. Ft. ³ | | | | | | | | | | | | |
| 1/4" | | | 4 | | | | | | | | | |
| 3/16" | | | 8 | | | 20 | | | | | | |
| 1/4" | | | 10 | | | 32 | | | 50 | | | |
| 3/8" | 14 | 14 | 14 | 42 | 42 | 42 | 80 | 80 | 80 | 140 | 140 | |
| 1/2" | 20 | 20 | 20 | 62 | 62 | 62 | 105 | 105 | 105 | 180 | 180 | 180 |
| 5/8" | 25 | 25 | 25 | 62 | 62 | 62 | 130 | 130 | 130 | 215 | 215 | 215 |
| 3/4" | 30 | 30 | 30 | 72 | 72 | 72 | 155 | 155 | 155 | 250 | 250 | 250 |
| 7/8" | | | | 80 | 80 | 80 | 180 | 180 | 180 | 280 | 280 | 280 |
| 1" | | | | 85 | 85 | 85 | 205 | 205 | 205 | 310 | 310 | 310 |

NOTES: 1. All capacities based on data shown in general crusher notes.
 2. Capacities of Style FC Gyroscopes are based on CLOSED CIRCUIT crushing—not finished product.

CONO 3 FT PARA ACABADO FINOS, REQUIERE MOTOR DE 100 HP, CAPACIDADES APROX. 3/16 20 TON, 1/4 32 TON, 3/8 42 TON, 1/2 52 TON, 5/8 62 TON, 3/4 72 TON, 7/8 80 TON, 1 PULGADA 95 TON, PESO 25000 LBS, , - -