



Venta de Maquinaria Industrial y Agrícola
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: (625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 16405

PERFORADORA BMC MH428

BMC

MH42

0000

12150



THE BMC HYDRA-HAMMER IS BUILT TO THESE STRICT SPECIFICATIONS	
GENERAL INFORMATION	
WEIGHT	5500 lbs
Approx. (L x W x H)	
OVERALL LENGTH	13'3"
Working Position	14'7"
Wheel Base	9'2 1/2"
WHEEL BASE	7'8"
OVERALL WIDTH	14'4"
OVERALL HEIGHT	7'8"
Working Position	8'2 1/2"
Wheel Height	8'10"
with cap	8'10"
with cap	8'10"
MAXIMUM ROAD SPEED	35 mph
CHASSIS	
Large, reinforced metal steps provide easy access.	
Four 2000 lbs. 1000 lb. 2000 lb. 8 cylinders, 97 hp at 2600 RPM.	
CLUTCH	
11" diameter hydraulically actuated.	
Adjust forward, 1" reverse, synchronizer.	
CREEP DRIVE: 35 mph from 1000 rpm.	
REAR DRIVING AXLE	10,000 lbs. cap
Dual wheels, hydraulic power-steering mechanism.	
FRONT STEERING AXLE	3,500 lbs. cap
Single wheels, tie rod action.	
TIRES	
16" driving wheels, 150x70, anti-grip tube type.	
16" drive wheels, 800x16, 160x65, 160x65, 160x65.	
STEERING	
16" hydraulic power.	
BRAKES	
Hydraulic.	
FRAME	
One-piece, welded steel construction.	
FUEL TANK	
30 gal., full ten-hour supply.	
DRIVE	
34 ft. stroke per minute to 240 minimum length stroke per minute.	
HAMMER HEIGHT: 3000 lbs.	
CONTROLS	
Hydraulic operation for lower elevation, swing, hammer lift, chassis lift, and lower traverse.	
ROCKETS	
Two, 1000 lbs. hydraulic lifting chassis. Provides 10" lift to either side.	
TOWER FRAME	
Hydraulic motor powered traverse chain provides 810° of rotation, lift, swing, travel.	
CREEP DRIVE	
Hydraulic motor driving through the creep gear box provides speeds at 1/4, 1/2, and 3/4 of normal.	
DUAL RANGE HAMMER CONTROL	
Increases dig power by allowing both normal high-speed operation of hammer to cut.	
HYDRAULIC SYSTEM	
ROCKER PUMP	
Continuously driven from engine overhead. Delivers 30.0 GPM at 2000 psi for hammer actuation and 16 GPM at 2000 psi for all other functions.	
HYDRAULIC RESERVOIR	
40 gal., 40 gal. cap. Equipped with suction strainer and in-line return line filter.	
CONTROL VALVES	
Designed for 2000 psi. Complete with anti-siphon relief and cushion systems.	
OPTIONAL EQUIPMENT	
ALL WEATHER CAB WITH HEATER	
DIESEL ENGINE	
WINDSHIELD AND	
ROCK OFF ALARM	
TOOLS	
Temp. head, demolition tools, and cutting blades.	

CON MOTOR JOHN DEERE A DIESEL 4 CILINDROS, VELOCIDAD 35 MPH, PESO 9,590 LBS, - -