



- Venta de Maquinaria Industrial y Agrícola -
 Km 24 Carr. Alvaro Obregón
 Cd. Cuauhtemoc, Chih.

Tels: (625) 586 6477 y 52 (625) 586 6412
 Cels: 625) 590 8941 - (625) 115 4764 - (625) 134 4523
 Cels: (625) 100 1010 - (625) 283 9741
 E-mails: awiebe71@hotmail.com, ventas@maquinariaw.com.mx

No. Folio: 5333

PAVIMENTADORA

LAYTON

F-525

1987

F-9959-N-7



F-525
MISCELLANEOUS SPECIFICATIONS
 Height 5'4"
 Length 65'
 Width 5'
 Spread depth 6" to 4" 10"
 Screen width 2' - 12"
 Operation speed 1/2 wide 2' deep, 100 per minute
 Weight (Basic Machine) 3000 lbs. (approx.)

ENGINES
 2 heavy-duty vertical shaft Tecumseh 7 hp, standard
 Electric starter standard
 Alternator (AMF) standard
 Hand pump for oil standard
 Fuel tank standard
 Fuel tank capacity 10 gal. iron cylinder liner standard

FUEL SYSTEM
 Propane 10 gal. tank supplies a
 common fuel for both engines and optional spread
 heater

HITCH ARMS
 Heavy-duty alloy steel standard
 tapered roller bearings in rim rolls standard
 Roller thrust bearings in side rolls standard

CONTROLS
 Hitches hand pump or electric hydraulic, unit
 Shut-off gate hand pump or electric hydraulic, unit
 Spread extension hand pump or electric hydraulic, unit
 Screen extension manual
 Depth controls manual
 Augers dual control, toggle switches

AUGERS
 Material cast chrome alloy iron
 Auger flight 3/8" thick, 20" long, 3" diameter
 Double roller chain drive standard
 Shaft 2 3/8" diameter, A14 alloy steel
 Speed 150 rpm
 Installation low in hopper with
 external target bearings

UNDERCARRIAGE
 Dual drive in tandem sets of dual tandem pneumatic
 tires 5.30 x 6 ply mounted in line
 Each set walking beam mounted standard

HOPPER
 Capacity 3 tons
 Shut-off gate coordinated double clamped type
 Shut-off gate with 1/2" overlap standard
 Hopper opening 13 1/2"

SCREED PLATE
 Non-iron gate, replaceable standard
 Hardness 360-400 Brinell
 Thickness 3/16"
 Heat treated, abrasion resistant standard
 Tensile strength 190,000 p.s.i.

SCREED CROWN & INVERT
 Ratchet operated both trailing and leading
 edge controlled simultaneously standard
 Accurately dimensioned

SCREED HOIST
 Hydraulic operated

HYDRAULIC SYSTEM
 One engine driven pump for each side
 Work lines, shut-off gate, spread foot, manual hand
 pump, electric hydraulic unit

OPTIONAL EQUIPMENT
 Electric Hydraulic System
 2000 lbs. battery powered, charged by engine
 Alternator, hand pump backup system
 Spread heater
 2 burner externally mounted
 burner
 Dual Plate
 Attach to spread extension
 45" wide from 2' to 4' wide
 Hydraulic Powered Extensions (Electric action only)
 Extension covered by engine oil and fuel dip
 Joint Matching Extensions
 Two drive
 Attach to end of work
 Each drive with 1000
 Adjustable Hinge Arms
 Adjustable in 3 inch



Precio: 4,750.00 USD mas IVA